

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 04/07/2015

1 Identification

- · Product identifier
- · Trade name: R600 Mixed
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

EcoGreen Industries, LLC

PO Box 1308

Anderston, CA 96007 Phone: (530) 378-4443 Fax: (888) 612-3207

· Emergency telephone number: Chemtrec 800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 1 H224 Extremely flammable liquid and vapor.

- · Label elements
- GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

Extremely flammable liquid and vapor.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:

30 percent of the mixture consists of ingredient(s) of unknown toxicity.

(Contd. on page 2)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 04/07/2015

Trade name: R600 Mixed

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 1 Fire = 4 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1Fire = 4Reactivity = 0

· Other hazards None known

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous Components:					
CAS: 106-97-8 RTECS: EJ 4200000	Butane	♠ Flam. Gas 1, H220; Press. Gas, H280	60-90%		
CAS: 74-98-6 RTECS: TX 2275000	Propane	♠ Flam. Gas 1, H220; Press. Gas, H280	25-50%		

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 04/07/2015

Trade name: R600 Mixed

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of the collected material according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling:
- · Precautions for safe handling Open and handle receptacle with care.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

· Co	· Components with occupational exposure limits:				
106-97-8 Butane					
RE	L Long-term value: 1900 mg/m³, 800 ppm				
TL	/ Short-term value: 2370 mg/m³, 1000 ppm				
74-98-6 Propane					
PE	L Long-term value: 1800 mg/m³, 1000 ppm				
RE	Long-term value: 1800 mg/m³, 1000 ppm				
TL	refer to Appendix F				

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/07/2015 Reviewed on 04/07/2015

Trade name: R600 Mixed

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:
Color:
Color:
Coloress
Odor:
Petroleum-like
Not determined.

pH-value:
Not determined.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
-44 °C (-47 °F)
-97 °C (-143 °F)
-97 °C (-143 °F)
Not applicable.
-Ignition temperature:
-365 °C (689 °F)
-Decomposition temperature:
Not determined.

· **Auto igniting:** Product is not self-igniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor

mixtures are possible.

· Explosion limits:

Lower: 1.5 Vol % **Upper:** 10.9 Vol %

Vapor pressure @ 20 °C (68 °F):
 Density @ 20 °C (68 °F):
 8300 hPa (6226 mm Hg)
 0.002 g/cm³ (0.017 lbs/gal)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/07/2015 Reviewed on 04/07/2015

Trade name: R600 Mixed

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents:100.0 %VOC content:70.0 %

· Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Heat, flame and ignition sources.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values that are relevant for classification:

106-97-8 Butane

Inhalative LC50/4 h 658 mg/l (rat)

- · Primary irritant effect:
- · on the skin: No irritating effect.
- · on the eye: No irritating effect.
- Additional toxicological information:
- Carcinogenic categories

· IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/07/2015 Reviewed on 04/07/2015

Trade name: R600 Mixed

- · Additional ecological information:
- · General notes: Generally not hazardous for water
- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.*vPvB:* Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· **DOT, ADR, IMDG, IATA** UN1965

UN proper shipping name

· **DOT** Hydrocarbon gas mixture, liquefied, n.o.s.

ADR
 UN1965 Hydrocarbon gas mixture, liquefied, n.o.s.
 IMDG, IATA
 HYDROCARBON GAS MIXTURE, LIQUEFIED, N.O.S.

· Transport hazard class(es)

· DOT, IMDG, IATA

· *Class* 2.1

· ADR

· *Class* 2.1 2F

· Packing group

· **DOT, ADR, IMDG, IATA** Non-Regulated Material

Environmental hazards: Not applicable. Special precautions for user Not applicable.

· Danger code (Kemler): 23

· **EMS Number:** F-D ,S-U

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

• Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation": UN1965, Hydrocarbon gas mixture, liquefied, n.o.s., 2.1

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

ate 04/07/2015 Reviewed on 04/07/2015

Trade name: R600 Mixed

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

Extremely flammable liquid and vapor.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves / eve protection / face protection.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

State Right to Know



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/07/2015 Reviewed on 04/07/2015

Trade name: R600 Mixed

CAS: 74-98-6 RTECS: TX 2275000	Propane	Flam. Gas 1, H220; Press. Gas, H280	25-50%
All ingredients are list	ed.		

[·] Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

<u>16 Other information</u>

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- · Date of preparation / last revision 04/07/2015 / -
- Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1 Press. Gas: Gases under pressure: Compressed gas Flam. Liq. 1: Flammable liquids, Hazard Category 1

* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106