



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/20/2017 Reviewed on 07/20/2017

1 Identification

- · Product Identifier
- · Trade name: 40/40/20 Mixed
- Relevant identified uses of the substance or mixture and uses advised against:
- · **Product Description** No further relevant information
- · Details of the Supplier of the Safety Data Sheet:
- Manufacturer/Supplier:

EcoGreen Industries, LLC

PO Box 1308

Anderson, CA 96007 Phone: (530) 378-4443 Fax: (888) 612-3207

· Emergency telephone number: Chemtrec 800-424-9300

2 Hazard(s) Identification

· Classification of the substance or mixture:



Flam. Gas 1 H220 Extremely flammable gas.

- · Label elements:
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:



GHS02

- · Signal word: Danger
- · Hazard statements:

H220 Extremely flammable gas.

· Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 Eliminate all ignition sources if safe to do so.

P403 Store in a well-ventilated place.

· Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

60 % of the mixture consists of component(s) of unknown toxicity.

- · Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 4 Reactivity = 0



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/20/2017 Reviewed on 07/20/2017

Trade name: 40/40/20 Mixed

· HMIS-ratings (scale 0 - 4)



· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of substances listed below with non-hazardous additions.

· Dangerous Components:			
CAS: 75-28-5 RTECS: TZ 4300000	Isobutane	Flam. Gas 1, H220; Press. Gas, H280	25–50%
CAS: 106-97-8 RTECS: EJ 4200000	Butane	♦ Flam. Gas 1, H220; Press. Gas, H280	25–50%
CAS: 74-98-6 RTECS: TX 2275000	Propane	Flam. Gas 1, H220; Press. Gas, H280	15–35%

· Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

- · Description of first aid measures:
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Generally the product does not irritate the skin.

If skin irritation occurs, consult a doctor.

· After eve contact:

Rinse opened eye for several minutes under running water.

If eye irritation occurs, consult a doctor.

- · After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-Fighting Measures

- Extinguishing media:
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture: No further relevant information available.
- Advice for firefighters:
- Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

(Contd. on page 3)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/20/2017 Reviewed on 07/20/2017

Trade name: 40/40/20 Mixed

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: No special measures required.
- Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of the collected material according to regulations.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

FIOLECTIV	e Action Criteria for Chemicais	
· PAC-1:		
75-28-5	Isobutane	5500* ppm
106-97-8	Butane	5500* ppm
74-98-6	Propane	5500* ppm
PAC-2:		
75-28-5	Isobutane	17000** ppm
106-97-8	Butane	17000** ppm
74-98-6	Propane	17000** ppm
PAC-3:		
75-28-5	Isobutane	53000*** ppm
106-97-8	Butane	53000*** ppm
74-98-6	Propane	33000*** ppm

<u>7 Han</u>dling and Storage

- · Handling
- Precautions for safe handling: Open and handle receptacle with care.
- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities:
- · Storage
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s): No further relevant information available.

(Contd. on page 4)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/20/2017 Reviewed on 07/20/2017

Trade name: 40/40/20 Mixed

8 Exposure Controls/Personal Protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters:
- · Components with occupational exposure limits:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits

	At this time, the remaining constituent has no known exposure limits.		
75-28-5 Isobutane			
	TLV	Short-term value: (2370) mg/m³, (1000) ppm NIC-EX	
74-98-6 Propane			
	PEL	Long-term value: 1800 mg/m³, 1000 ppm	
	REL	Long-term value: 1800 mg/m³, 1000 ppm	
	TLV	refer to Appendix F inTLVs&BEIs book; NIC-EX	
106-97-8 Butane (40%)		97-8 Butane (40%)	
	REL	Long-term value: 1900 mg/m³, 800 ppm	
	TLV	Short-term value: 2370 mg/m³, 1000 ppm (EX)	

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls:
- Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation.
- · Protection of hands: Not required.
- · Material of gloves: Not required.
- · Penetration time of glove material: Not applicable.
- · Eye protection:



Tightly sealed goggles

9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:
Color:
Color:
Colorless
Odor:
Petroleum-like
Not determined.

· **pH-value:** Not determined.

(Contd. on page 5)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/20/2017 Reviewed on 07/20/2017

Trade name: 40/40/20 Mixed

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
-44°C (-47°F)

-97°C (-143°F)

Not determined.
-44°C (-47°F)

Not applicable.

Ignition temperature:
460°C (860°F)

· **Auto igniting:** Product is not self-igniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapor

mixtures are possible.

Not determined.

· Explosion limits:

Lower: 1.7 Vol % **Upper:** 10.9 Vol %

· Vapor pressure @ 20°C (68 °F): 8300 hPa (6226 mm Hg)

• **Density @ 20°C (68 °F):** 0.385 g/cm³ (3.213 lbs/gal)

Relative density: Not determined.
 Vapor density: Not determined.
 Evaporation rate: Not determined.

· Solubility in / Miscibility with:

· Decomposition temperature:

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents: 30.0 % VOC content: 70.0 %

269.4 g/l / 2.25 lb/gl

• Other information: No further relevant information available.

10 Stability and Reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: Heat, flame and ignition sources.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/20/2017 Reviewed on 07/20/2017

Trade name: 40/40/20 Mixed

11 Toxicological Information

- Information on toxicological effects:
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

106-97-8 Butane

Inhalative LC50/4 h 658 mg/l (Rat)

- · Primary irritant effect:
- · On the skin: No irritating effect.
- · On the eye: No irritating effect.
- Additional toxicological information:
- · Carcinogenic categories:
- · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

* 12 Ecological Information

- Toxicity:
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability: No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- Additional ecological information:
- · General notes: Generally not hazardous for water.
- · Results of PBT and vPvB assessment:
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects: No further relevant information available.

13 Disposal Considerations

- · Waste treatment methods:
- · Recommendation:

Observe all federal, state and local environmental regulations when disposing of this material.

- · Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

14 Transport Information

- · UN-Number:
- · DOT, ADR/ADN, IMDG, IATA

UN1965

· UN proper shipping name:

· DOT

Hydrocarbon gas mixture, liquefied, n.o.s.

(Contd. on page 7)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/20/2017 Reviewed on 07/20/2017

Trade name: 40/40/20 Mixed

ADR/ADN
 UN1965 Hydrocarbon gas mixture, liquefied, n.o.s.
 IMDG, IATA
 HYDROCARBON GAS MIXTURE, LIQUEFIED, N.O.S.

· Transport hazard class(es):

· DOT



· *Class:* 2.1 · *Label:* 2.1

· ADR/ADN



• Class: 2.1 2F • Label: 2.1

· IMDG, IATA



· Class: 2.1 · Label: 2.1

Packing group:
 Environmental hazards:
 Special precautions for user:
 Not applicable.
 Not applicable.

Danger code (Kemler):
 EMS Number:
 Stowage Category

23

F-D,S-U

E

· **Stowage Code** SW2 Clear of living quarters.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.

· Transport/Additional information:

· DOT

• **Quantity limitations:**On passenger aircraft/rail: Forbidden
On cargo aircraft only: 150 kg

· ADR/ADN

· Excepted quantities (EQ): Code: E0

Not permitted as Excepted Quantity

· IMDG

· Limited quantities (LQ): 0

Excepted quantities (EQ): Code: E0

Not permitted as Excepted Quantity

(Contd. on page 8)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/20/2017 Reviewed on 07/20/2017

Trade name: 40/40/20 Mixed

· UN "Model Regulation": UN 1965 HYDROCARBON GAS MIXTURE, LIQUEFIED,

N.O.S., 2.1

15 Regulatory Information

- Safety, health and environmental regulations/legislation specific for the substance or mixture:
- SARA (Superfund Amendments and Reauthorization):
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act):

All ingredients are listed or exempt from listing.

- · California Proposition 65:
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

New Jersey Right-to-Know List:

All ingredients are listed.

New Jersey Special Hazardous Substance List:

75-28-5		F4
106-97-8	Butane	F4
74-98-6	Propane	F4

· Pennsylvania Right-to-Know List:

All ingredients are listed.

· Pennsylvania Special Hazardous Substance List:

None of the ingredients are listed.

- · Carcinogenic categories:
- · EPA (Environmental Protection Agency):

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH):

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/20/2017 Reviewed on 07/20/2017

Trade name: 40/40/20 Mixed

Hazard pictograms:



- · Signal word: Danger
- Hazard statements:

H220 Extremely flammable gas.

· Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 Eliminate all ignition sources if safe to do so.

P403 Store in a well-ventilated place.

· National regulations:

None of the ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision: 07/20/2017 / 4

Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Gas 1: Flammable gases - Category 1

Press. Gas: Gases under pressure – Compressed gas

* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106